

GP Batteries

PRODUCT SPECIFICATION

GP Portable PowerBank Model : FP05M-A

Revision History

Revision	Date	Initiator	Reason for Change
0.0	18 Aug 2015	CC Li	Initial release as Preliminary Spec
1.0	30 Sep 2015	CC Li	1 st version release Dis-charging time revised to 1H Charging time revised to 5H

Prepared By	Approved By
CC Li	Wilfred Kong
Date: 30 Sep, 2015	Date: 30 Sep, 2015


GPI International Limited

Gold Peak Building, 8/F, 30 Kwai Wing Road,
Kwai Chung, New Territories, Hong Kong.
Tel: (852) 2484 3333 Fax: (852) 24805912
Email: gpi@goldpeak.com
Website: <http://www.gpbatteries.com>

GP Batteries

Product Specification

Model no.: FP05M-A



2 in 1 Cable applicable for both Apple and USB powered device

Product Name	:	GP Portable PowerBank FP05M-A with 2 in 1 MFi cable
Description	:	Back up power for Iphone, Ipad & USB powered electronic devices (e.g. smartphones, tablet PCs)
Battery Rating	:	Lithium polymer 3.7V 5000mAh 18.5Wh
Input	:	2A / 5V DC
Output	:	2.1A / 5V DC
Application	:	Charge Iphone, Ipad and USB powered electronic devices
Recharging Time	:	5 hours (approx.) by 5V/2A
Discharging Time	:	1 hours (approx.) at 2A (The discharging time may vary for different devices)
Operation Temperature	:	5°C to 40°C
Safety protection	:	1) Over and under temperature protection 2) Over current protection 3) Over charging protection 4) Over discharging protection 5) Short circuit protection

GP Batteries

Product Specification

Model no.: FP05M-A

LED Indication : **Charging & Discharging the Portable PowerBank**

Table 1

Charging & Discharging Condition	LED Indicator
Charging	Last LED Slow Flashing
Discharging	Refer to battery status (Table 2)
Fully charged	All On in Green
Errors	Red LED fast flashing

Press button to show battery status :

Table 2

Battery Strength	LED indicator
Good	Four LED on
Good to average	First Three LED on
Average	First Two LED on
Weak	One LED on
Very Weak	One LED fast flashing
No Power	No LED

Dimensions : 120 (L) x 66 (W) x 13 (H) mm

Weight : 162.5g +/- 10g (approx.)

Certification : CE, FCC, UN38.3

Warranty Period : 12 months from ex-factory date